

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0 0 20px;">Manufacturing test</p> <p style="margin: 5px 0 0 20px;">WetWet test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr><td style="border-bottom: 1px solid black;">Machine:</td><td style="border-bottom: 1px solid black;">2MESC203AH</td></tr> <tr><td style="border-bottom: 1px solid black;">Serial Nr:</td><td style="border-bottom: 1px solid black;">201901510</td></tr> <tr><td style="border-bottom: 1px solid black;">Waferlot Nr:</td><td style="border-bottom: 1px solid black;">180806</td></tr> <tr><td style="border-bottom: 1px solid black;">Tubing:</td><td style="border-bottom: 1px solid black;">CUTTER: wet-wet</td></tr> <tr><td style="border-bottom: 1px solid black;">Date:</td><td style="border-bottom: 1px solid black;">10-Jan-2019</td></tr> <tr><td style="border-bottom: 1px solid black;">Tested by:</td><td style="border-bottom: 1px solid black;">Carl De Vos</td></tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180806	Tubing:	CUTTER: wet-wet	Date:	10-Jan-2019	Tested by:	Carl De Vos
Machine:	2MESC203AH												
Serial Nr:	201901510												
Waferlot Nr:	180806												
Tubing:	CUTTER: wet-wet												
Date:	10-Jan-2019												
Tested by:	Carl De Vos												

Test WetWet connection

Tensile Strength (N)

1	86.7	
2	104.3	
3	94.4	
4	85.4	
5	91.3	
6	94.2	
7	100.0	
8	102.2	
9	87.4	
10	87.1	Limits
Average	93.3	≥ 45
Minimum	85.4	≥ 40
Stdev	6.9	

Weldtester: 001
 Serial number traction: 3343K1819
 Calibration of tensile strength tester
 Last Calibration: Mar-2018

Conclusion
Passed according to the acceptance limit

Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.

Signature Test Engineer 	Initials & Signature Reviewer
-----------------------------	-----------------------------------

TEST REPORT

Manufacturing test

DryDry test

Machine: **2MESC203AH**
 Serial Nr: **201901510**
 Waferlot Nr: **180806**
 Tubing: **Fresenius Kabi Dry-Dry**
 Date: **10-Jan-2019**
 Tested by: **Carl De Vos**

Test DryDry connection

Tensile Strength (N)

1	129.1	
2	133.8	
3	144.8	
4	145.0	
5	126.1	
6	133.5	
7	131.0	
8	120.0	
9	136.7	
10	143.1	Limits
Average	134.3	≥ 40
Minimum	120.0	≥ 40
Stdev	8.3	

Serial number traction: 3343K1819
 Calibration of tensile strength tester
 Last Calibration: Mar-2018

Conclusion

Passed according to the acceptance limit

Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.

Signature Test Engineer

Initials & Signature Reviewer

PER IP-3042

Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use. Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in the Device History Record of this device.

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0 0 0;">Manufacturing test</p> <p style="margin: 5px 0 0 0;">DryWet test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black;">Machine:</td> <td style="border-bottom: 1px solid black;">2MESC203AH</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Serial Nr:</td> <td style="border-bottom: 1px solid black;">201901510</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Waferlot Nr:</td> <td style="border-bottom: 1px solid black;">180806</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tubing:</td> <td style="border-bottom: 1px solid black;">Fresenius Kabi dry-wet</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Date:</td> <td style="border-bottom: 1px solid black;">10-Jan-2019</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tested by:</td> <td style="border-bottom: 1px solid black;">Carl De Vos</td> </tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180806	Tubing:	Fresenius Kabi dry-wet	Date:	10-Jan-2019	Tested by:	Carl De Vos
Machine:	2MESC203AH												
Serial Nr:	201901510												
Waferlot Nr:	180806												
Tubing:	Fresenius Kabi dry-wet												
Date:	10-Jan-2019												
Tested by:	Carl De Vos												

Test DryWet connection
Tensile Strength (N)

1	127.5		11	139.2	
2	126.2		12	132.1	
3	128.5		13	140.6	
4	139.3		14	138.0	
5	131.1		15	135.5	
6	133.4		16	129.2	
7	134.8		17	140.6	
8	141.9		18	135.8	
9	136.7		19	135.1	
10	137.2		20	113.0	Limits
	Average		133.8		≥ 40
	Minimum		113.0		≥ 40
	Stdev		6.7		

Serial number traction: 3343K1819
 Calibration of tensile strength tester
 Last Calibration: Mar-2018

Conclusion

Passed according to the acceptance limit

Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.



Signature Test Engineer 	Initials & Signature Reviewer
-----------------------------	-----------------------------------

PER IP-3042

*Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use
 Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in
 the Device History Record of this device.*

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0;">Manufacturing test</p> <p style="margin: 5px 0;">DryDry test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr><td style="border-bottom: 1px solid black;">Machine:</td><td style="border-bottom: 1px solid black;">2MESC203AH</td></tr> <tr><td style="border-bottom: 1px solid black;">Serial Nr:</td><td style="border-bottom: 1px solid black;">201901510</td></tr> <tr><td style="border-bottom: 1px solid black;">Waferlot Nr:</td><td style="border-bottom: 1px solid black;">180604</td></tr> <tr><td style="border-bottom: 1px solid black;">Tubing:</td><td style="border-bottom: 1px solid black;">TERUMO TR-7: dry-dry</td></tr> <tr><td style="border-bottom: 1px solid black;">Date:</td><td style="border-bottom: 1px solid black;">10-Jan-2019</td></tr> <tr><td style="border-bottom: 1px solid black;">Tested by:</td><td style="border-bottom: 1px solid black;">Carl De Vos</td></tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180604	Tubing:	TERUMO TR-7: dry-dry	Date:	10-Jan-2019	Tested by:	Carl De Vos																											
Machine:	2MESC203AH																																							
Serial Nr:	201901510																																							
Waferlot Nr:	180604																																							
Tubing:	TERUMO TR-7: dry-dry																																							
Date:	10-Jan-2019																																							
Tested by:	Carl De Vos																																							
<p><u>Test DryDry connection</u></p> <p>Tensile Strength (N)</p> <table border="1" style="margin: auto; border-collapse: collapse;"> <tr><td style="width: 20px; text-align: center;">1</td><td style="width: 100px; text-align: center;">94.5</td><td></td></tr> <tr><td style="text-align: center;">2</td><td style="text-align: center;">83.9</td><td></td></tr> <tr><td style="text-align: center;">3</td><td style="text-align: center;">83.4</td><td></td></tr> <tr><td style="text-align: center;">4</td><td style="text-align: center;">95.7</td><td></td></tr> <tr><td style="text-align: center;">5</td><td style="text-align: center;">100.1</td><td></td></tr> <tr><td style="text-align: center;">6</td><td style="text-align: center;">98.0</td><td></td></tr> <tr><td style="text-align: center;">7</td><td style="text-align: center;">87.0</td><td></td></tr> <tr><td style="text-align: center;">8</td><td style="text-align: center;">87.6</td><td></td></tr> <tr><td style="text-align: center;">9</td><td style="text-align: center;">86.7</td><td></td></tr> <tr><td style="text-align: center;">10</td><td style="text-align: center;">89.6</td><td style="text-align: center;">Limits</td></tr> <tr><td style="text-align: center;">Average</td><td style="text-align: center;">90.6</td><td style="text-align: center;">≥ 73.6</td></tr> <tr><td style="text-align: center;">Minimum</td><td style="text-align: center;">83.4</td><td style="text-align: center;">≥ 53.9</td></tr> <tr><td style="text-align: center;">Stdev</td><td style="text-align: center;">6.0</td><td></td></tr> </table>		1	94.5		2	83.9		3	83.4		4	95.7		5	100.1		6	98.0		7	87.0		8	87.6		9	86.7		10	89.6	Limits	Average	90.6	≥ 73.6	Minimum	83.4	≥ 53.9	Stdev	6.0	
1	94.5																																							
2	83.9																																							
3	83.4																																							
4	95.7																																							
5	100.1																																							
6	98.0																																							
7	87.0																																							
8	87.6																																							
9	86.7																																							
10	89.6	Limits																																						
Average	90.6	≥ 73.6																																						
Minimum	83.4	≥ 53.9																																						
Stdev	6.0																																							
<p>Serial number traction: 3343K1819</p> <p>Calibration of tensile strength tester</p> <p>Last Calibration: Mar-2018</p>																																								
<p><u>Conclusion</u></p> <p>Passed according to the acceptance limit</p>																																								
<p>Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.</p>																																								
Signature Test Engineer	Initials & Signature Reviewer																																							
																																								

PER IP-3042

*Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use
 Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in
 the Device History Record of this device.*

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0;">Manufacturing test</p> <p style="margin: 5px 0;">DryWet test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black;">Machine:</td> <td style="border-bottom: 1px solid black;">2MESC203AH</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Serial Nr:</td> <td style="border-bottom: 1px solid black;">201901510</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Waferlot Nr:</td> <td style="border-bottom: 1px solid black;">180604</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tubing:</td> <td style="border-bottom: 1px solid black;">TERUMO TR-7: dry-wet</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Date:</td> <td style="border-bottom: 1px solid black;">10-Jan-2019</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tested by:</td> <td style="border-bottom: 1px solid black;">Carl De Vos</td> </tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180604	Tubing:	TERUMO TR-7: dry-wet	Date:	10-Jan-2019	Tested by:	Carl De Vos																																																					
Machine:	2MESC203AH																																																																	
Serial Nr:	201901510																																																																	
Waferlot Nr:	180604																																																																	
Tubing:	TERUMO TR-7: dry-wet																																																																	
Date:	10-Jan-2019																																																																	
Tested by:	Carl De Vos																																																																	
<p><u>Test DryWet connection</u></p> <p>Tensile Strength (N)</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border: 1px solid black; padding: 2px;">1</td> <td style="border: 1px solid black; padding: 2px;">100.8</td> <td style="border: 1px solid black; padding: 2px;">11</td> <td style="border: 1px solid black; padding: 2px;">98.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">2</td> <td style="border: 1px solid black; padding: 2px;">92.3</td> <td style="border: 1px solid black; padding: 2px;">12</td> <td style="border: 1px solid black; padding: 2px;">89.6</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">3</td> <td style="border: 1px solid black; padding: 2px;">87.5</td> <td style="border: 1px solid black; padding: 2px;">13</td> <td style="border: 1px solid black; padding: 2px;">95.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">4</td> <td style="border: 1px solid black; padding: 2px;">91.1</td> <td style="border: 1px solid black; padding: 2px;">14</td> <td style="border: 1px solid black; padding: 2px;">78.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">5</td> <td style="border: 1px solid black; padding: 2px;">94.2</td> <td style="border: 1px solid black; padding: 2px;">15</td> <td style="border: 1px solid black; padding: 2px;">87.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">6</td> <td style="border: 1px solid black; padding: 2px;">90.3</td> <td style="border: 1px solid black; padding: 2px;">16</td> <td style="border: 1px solid black; padding: 2px;">90.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">7</td> <td style="border: 1px solid black; padding: 2px;">93.3</td> <td style="border: 1px solid black; padding: 2px;">17</td> <td style="border: 1px solid black; padding: 2px;">81.6</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">8</td> <td style="border: 1px solid black; padding: 2px;">92.8</td> <td style="border: 1px solid black; padding: 2px;">18</td> <td style="border: 1px solid black; padding: 2px;">89.2</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">9</td> <td style="border: 1px solid black; padding: 2px;">89.0</td> <td style="border: 1px solid black; padding: 2px;">19</td> <td style="border: 1px solid black; padding: 2px;">95.3</td> <td></td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">10</td> <td style="border: 1px solid black; padding: 2px;">97.3</td> <td style="border: 1px solid black; padding: 2px;">20</td> <td style="border: 1px solid black; padding: 2px;">79.5</td> <td style="border: 1px solid black; padding: 2px;">Limits</td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 2px;">Average</td> <td style="border: 1px solid black; padding: 2px;">90.7</td> <td style="border: 1px solid black; padding: 2px;">≥ 70</td> <td></td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 2px;">Minimum</td> <td style="border: 1px solid black; padding: 2px;">78.3</td> <td style="border: 1px solid black; padding: 2px;">≥ 49</td> <td></td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 2px;">Stdev</td> <td style="border: 1px solid black; padding: 2px;">5.9</td> <td></td> <td></td> </tr> </table>		1	100.8	11	98.3		2	92.3	12	89.6		3	87.5	13	95.3		4	91.1	14	78.3		5	94.2	15	87.3		6	90.3	16	90.3		7	93.3	17	81.6		8	92.8	18	89.2		9	89.0	19	95.3		10	97.3	20	79.5	Limits		Average	90.7	≥ 70			Minimum	78.3	≥ 49			Stdev	5.9		
1	100.8	11	98.3																																																															
2	92.3	12	89.6																																																															
3	87.5	13	95.3																																																															
4	91.1	14	78.3																																																															
5	94.2	15	87.3																																																															
6	90.3	16	90.3																																																															
7	93.3	17	81.6																																																															
8	92.8	18	89.2																																																															
9	89.0	19	95.3																																																															
10	97.3	20	79.5	Limits																																																														
	Average	90.7	≥ 70																																																															
	Minimum	78.3	≥ 49																																																															
	Stdev	5.9																																																																
<p>Serial number traction: 3343K1819</p> <p>Calibration of tensile strength tester</p> <p>Last Calibration: Mar-2018</p>																																																																		
<p><u>Conclusion</u></p> <p>Passed according to the acceptance limit</p>																																																																		
<p>Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.</p>																																																																		
<p style="text-align: center;">Signature Test Engineer</p>	<p style="text-align: center;">Initials & Signature Reviewer</p>																																																																	

PER IP-3042

*Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use
 Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in
 the Device History Record of this device.*

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0 0 0;">Manufacturing test</p> <p style="margin: 5px 0 0 0;">WetWet test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black;">Machine:</td> <td style="border-bottom: 1px solid black;">2MESC203AH</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Serial Nr:</td> <td style="border-bottom: 1px solid black;">201901510</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Waferlot Nr:</td> <td style="border-bottom: 1px solid black;">180604</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tubing:</td> <td style="border-bottom: 1px solid black;">Fresenius-Kabi wet-wet</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Date:</td> <td style="border-bottom: 1px solid black;">10-Jan-2019</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tested by:</td> <td style="border-bottom: 1px solid black;">Carl De Vos</td> </tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180604	Tubing:	Fresenius-Kabi wet-wet	Date:	10-Jan-2019	Tested by:	Carl De Vos
Machine:	2MESC203AH												
Serial Nr:	201901510												
Waferlot Nr:	180604												
Tubing:	Fresenius-Kabi wet-wet												
Date:	10-Jan-2019												
Tested by:	Carl De Vos												

Test WetWet connection

Tensile Strength (N)

1	102.6	
2	112.0	
3	101.2	
4	133.2	
5	128.0	
6	93.5	
7	94.5	
8	124.1	
9	102.3	
10	94.7	Limits
Average	108.6	≥ 40
Minimum	93.5	≥ 40
Stdev	14.8	

Weldtester: 001
 Serial number traction: 3343K1819
 Calibration of tensile strength tester
 Last Calibration: Mar-2018

Conclusion

Passed according to the acceptance limit

Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.

Signature Test Engineer 	Initials & Signature Reviewer
-----------------------------	-----------------------------------

PER IP-3042

*Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use
 Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in
 the Device History Record of this device.*

TERUMOBCT

Unlocking the Potential of Blood

<h2 style="margin: 0;">TEST REPORT</h2> <p style="margin: 5px 0;">Manufacturing test</p> <p style="margin: 5px 0;">WetWet test</p>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black;">Machine:</td> <td style="border-bottom: 1px solid black;">2MESC203AH</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Serial Nr:</td> <td style="border-bottom: 1px solid black;">201901510</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Waferlot Nr:</td> <td style="border-bottom: 1px solid black;">180604</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tubing:</td> <td style="border-bottom: 1px solid black;">TERUMO TR-7: wet-wet</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Date:</td> <td style="border-bottom: 1px solid black;">10-Jan-2019</td> </tr> <tr> <td style="border-bottom: 1px solid black;">Tested by:</td> <td style="border-bottom: 1px solid black;">Carl De Vos</td> </tr> </table>	Machine:	2MESC203AH	Serial Nr:	201901510	Waferlot Nr:	180604	Tubing:	TERUMO TR-7: wet-wet	Date:	10-Jan-2019	Tested by:	Carl De Vos																											
Machine:	2MESC203AH																																							
Serial Nr:	201901510																																							
Waferlot Nr:	180604																																							
Tubing:	TERUMO TR-7: wet-wet																																							
Date:	10-Jan-2019																																							
Tested by:	Carl De Vos																																							
<p><u>Test WetWet connection</u></p> <p>Tensile Strength (N)</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr><td style="border: 1px solid black; text-align: center;">1</td><td style="border: 1px solid black; text-align: center;">90.7</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">2</td><td style="border: 1px solid black; text-align: center;">88.9</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">3</td><td style="border: 1px solid black; text-align: center;">100.7</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">4</td><td style="border: 1px solid black; text-align: center;">85.0</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">5</td><td style="border: 1px solid black; text-align: center;">85.5</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">6</td><td style="border: 1px solid black; text-align: center;">91.9</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">7</td><td style="border: 1px solid black; text-align: center;">76.8</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">8</td><td style="border: 1px solid black; text-align: center;">96.7</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">9</td><td style="border: 1px solid black; text-align: center;">88.4</td><td></td></tr> <tr><td style="border: 1px solid black; text-align: center;">10</td><td style="border: 1px solid black; text-align: center;">77.9</td><td style="border: 1px solid black; text-align: center;">Limits</td></tr> <tr><td style="border: 1px solid black;">Average</td><td style="border: 1px solid black;">88.3</td><td style="border: 1px solid black;">≥ 50</td></tr> <tr><td style="border: 1px solid black;">Minimum</td><td style="border: 1px solid black;">76.8</td><td style="border: 1px solid black;">≥ 45</td></tr> <tr><td style="border: 1px solid black;">Stdev</td><td style="border: 1px solid black;">7.5</td><td></td></tr> </table>		1	90.7		2	88.9		3	100.7		4	85.0		5	85.5		6	91.9		7	76.8		8	96.7		9	88.4		10	77.9	Limits	Average	88.3	≥ 50	Minimum	76.8	≥ 45	Stdev	7.5	
1	90.7																																							
2	88.9																																							
3	100.7																																							
4	85.0																																							
5	85.5																																							
6	91.9																																							
7	76.8																																							
8	96.7																																							
9	88.4																																							
10	77.9	Limits																																						
Average	88.3	≥ 50																																						
Minimum	76.8	≥ 45																																						
Stdev	7.5																																							
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Weldtester:</td> <td>001</td> </tr> <tr> <td>Serial number traction:</td> <td>3343K1819</td> </tr> <tr> <td>Calibration of tensile strength tester</td> <td></td> </tr> <tr> <td>Last Calibration:</td> <td>Mar-2018</td> </tr> </table>		Weldtester:	001	Serial number traction:	3343K1819	Calibration of tensile strength tester		Last Calibration:	Mar-2018																															
Weldtester:	001																																							
Serial number traction:	3343K1819																																							
Calibration of tensile strength tester																																								
Last Calibration:	Mar-2018																																							
<p><u>Conclusion</u></p> <p>Passed according to the acceptance limit</p>																																								
<p>Remarks: The results on this test report are considered to remain unchanged up to the user's first operation. As such, the time span for preventive maintenance only starts after the user's first operation.</p>																																								
<p style="text-align: center;">Signature Test Engineer</p>	<p style="text-align: center;">Initials & Signature Reviewer</p>																																							

PER IP-3042

*Proprietary and Confidential - Do not use paper copies without verifying that the correct version is in use
 Duplicates of this test report are valid even if not signed. The signatures are on the original test report stored in
 the Device History Record of this device.*